Smart Connectivity

Catalog of Six Major Application Cables





LAN Cable Certificate


Blue point: with 3P POE++ certificate
 Red point: with UL-LP certificate

No.		Cable	Туре	PVC	LSOH	СМ	CMR	СМР
1	Cat.8	22AWG	S/FTP	•		•	•	•
2	Cat.8	26AWG	S/FTP	•		•	•	
3	Cat.7A	22AWG	S/FTP				•	•
4	Cat.7A	23AWG	S/FTP	•	•	•	•	•
5	Cat.7	23AWG	S/FTP	•	•		•	•
6	Cat.6A	23AWG	U/UTP	•	•	•	•	•
			U/UTP (Small OD)				•	•
			F/UTP	•	•	•	•	•
			S/FTP		•		•	•
7	Cat.6A	28AWG	U/UTP					•
	Cat.6A	28AWG	U/UTP		•	•	•	
8	Cat.6	22AWG	U/UTP				•	•
0	Cat.6	23AWG	U/UTP	•	•	٠	•	•
9			F/UTP	•	•	•	•	•
10	Cat.6	24AWG	U/UTP			•	•	٠
11	Cat.6	28AWG	U/UTP		•	•	•	
12	Cat.5e	24AWG	U/UTP	•	•	•	•	•
			F/UTP	•	•	•	•	•

Small OD (VTP) Cat.6A

- Overall Noise Control Barrier brings excellent alien crosstalk blocking and small overall diameter.
- Cat.6A performance, smaller overall diameter, efficient use of pathways and spaces.
- CMP OD 8.0 (0.315 inch) → 6.4mm (0.252 inch)
 CMP OD 8.3 (0.326 inch) → 7.0mm (0.283 inch)

Certification: UV CMP-LP (0.6A) 120W, CMR-LP (0.5A) 100W



www.wontex.com

CMX outdoor - CMP Cable

- Dual layer overall jacket.
- Designed for all-in-one indoor plenum and outdoor CMX cable.
- Can be pulled from the outdoors into the indoor directly.
- UTP(VTP) with Noise Control Barrier providing good protection from EMI noise.
- Cat.6 and Cat.6A performance.

Certification: UL 444(E142890) CMX, CM, CMP, CMX outdoor, CMX outdoor-CM, CMX outdoor-CMP UL 13(E122980) CL2X, CL3X, CL2, CL3, CL2P, CL3P and PLTC

UTP Cat.6A Direct Burial Cable

- Outdoor and direct burial purposes with gel-filled.
- Heavy pressure resistance and waterproof.
- Direct buried in smart green house, building to building applications.
- Dual-layer jacket with overall noise control barrier design to reduce alien crosstalk.

Certification: UV test 720HR, UL 13 Sec.35(crushinh test, 1000 lb)

-40°C Weather Resistant Cable

Special jacket material and overall design can withstand -40°C @ 4Hr cold impact test.

Certification: UL CITS -40°C @ 4hr Cold impact (GR-3164)

HDBaseT3.0 Cable

Web

More suitable for high-frequency video and audio data transmission.


- Transmit HDMI 2.0 uncompressed 4K/60Hz/4:4:4 audio and video.
- Support 4K HDR10+ Video and DOLBY VISION audio formats.
- Upgrade to 10G BaseT (Cat6A) Ethernet.


Certification: UL13 Sec.35 (Crushing Test, 1000 lb), UV resistance for 720 hours.





and more ...

Wonderful Hi-Tech Wonderful Hi-Tech Co., Ltd. (HQ) No. 72, Wugong 6th Road, New Taipei Industrial Park, Wugu District, New Taipei City, Taiwan









Tel +886-2-2298-8033

Mail sales@wontex.com.tw

) Wonderful Hi-Tech Co., Ltd.



For more info Scan here!



Energy Storage Cable



-**/**____D-

Large current 8~120mm²

High temperature rate Silicon, rubber, TPE insulation

> **Limited wiring space** Soft, thin copper, multiple cores

AWM	Insulation	Temp.	Voltage
3932	XLPE	125° C	2000V
10183	XLPVC	105°C	1000V
10070	PVC	105°C	600V
10269	PVC	105°C	1000V
3135	SR	200°C	600V

EV Charge Cable



Insulation & Jacket by TPE flexibility & durability

90°C or 105°C Temperature rate



釟

2 ~ 18 AWG Bare or Tinned copper



Weather Resistant Sunlight, -40°C cold bend








www.wontex.com

Solar Cable



Why Choose Us?

Wonderful Hi-Tech Advantages



Multi-Site Manufacturing (Taiwan/China/Thailand/Vietnam)

Experienced OEM MFR



Technical Support


Products are certified by International Lab



CCCA, TIA, BICSI Member

Product Diversity

Global Locations



Web www.wontex.com

Tel +886-2-2298-8033

New Taipei City, **Taiwan**

Wonderful Hi-Tech Co., Ltd.

Industrial

Robot Arm Cable

Industrial drag chain system, automatic production line , servo motor, logistics transmission equipment, numerical control machine.

2 to 20 million life times cycles.

Withstand 10 million times chain cycles without cracking and with a DCR increase of \leq 5%.

Feature

Flexibility &

Resistant

FEP-FEP CMP Cable





Heat

Resistant

Oil

Resistant

Bending / Torsion Resistant

FEP insulation, FEP jacket, foil shield with drain wire, CMP rating.

Designed for indoor and outdoor high temperature use, fireproof control cables.

NFPA 262 (CMP): temperature range: -40°C~200°C



Elexibility & Bending / Torsion Resistant

Electromagnetic Interference Resistant

Oil Resistant

Heat Resistant







323 0662

www.wontex.com

more info Scan here!

Wonderful Hi-Tech Co., Ltd. +886-2-2298-8033 Headquarters - No. 72, Wugong 6th Road, New Taipei Industrial Park, Wugu District, New Taipei City, Taiwan

CMX OUTDOOR-CMP Cable

Dual layer overall jacket.

All-in-one indoor plenum and outdoor CMX cable


UTP(VTP) with Noise Control Barrier providing good protection from EMI noise.


Supports Cat.6 and Cat.6A performance standards.



Certification:

UL 444 (E142890): CMX, CM, CMP, CMX outdoor, CMX outdoor-CM, CMX outdoor-CMP UL 13 (E122980): CL2X, CL3X, CL2, CL3, CL2P, CL3P and PLTC






Tel +886-2-2298-8033

Wonderful Hi-Tech Co., Ltd.






Coaxial Cable

- Provide reliable, high-quality signal transmission while ensuring the safety of the building's occupants in the event of a fire.
- BC or CCS conductor, Dual or Quad shield available.
- Cable designed for use in buildings with a plenum space or riser space.

Applications







www.wontex.com

Nylon wire (THHN/THWN)

- Excellent corrosive resistance, oil and gasoline resistance.
- Abrasion resistance and heat resistance.
- Rated temperature: 90°C dry and 75°C wet.
- Rated voltage: 600V

Applications

Internal wiring in electrical and electronic equipment Building

Lighting

High Temperature Wire

- Heat resistance, Oil resistance, Chemical resistance, Weather resistance, Non-flammable, Electrical stability.
- Temperatures ranging from -200°C to +250°C.
- Certification:
 EED: UL_style 1220

FEP: UL style 1330,1331,1332,10064 PFA: UL style 1726,1727, 10064,10231, 10362 ETFE: UL style 1867, 10064, 10231

Application: Chemical, electrical, automobile and medical applications

Lighting Control Cable


- Riser and Plenum are available.
- Certification: CL3R, CMR / CL3R, CMP

Access Control Cable

- All in a single cable: Card Reader, Door Contact, Request to exit and lock power, device connectivity in a single cable.
- Certification: CMP & CMR 75°C 300V

Speaker Cable

- For the electrical connections between speakers and amplifier sources.
- Certification: CM, CMR, CMP, CL2, CL3, CL3R, CL3P



and more ...



Wonderful Hi-Tech Co., Ltd. (HQ)

No. 72, Wugong 6th Road, New Taipei Industrial Park, Wugu District, New Taipei City, **Taiwan**



) Wonderful Hi-Tech Co., Ltd.

For more info Scan here!



Home Appliances



Type A USA / Canada / Japan



Type I Australia / New Zealand



Type E EU / Indonesia / Korea



Type O Thailand



Type G UK / Malaysia / Hong Kong



Type D India / Sri lanka

and more ...





www.wontex.com

Wonderful Hi-Tech Co., Ltd.+886-2-2298-8033Headquarters - No. 72, Wugong 6th Road, New Taipei Industrial Park, Wugu District, New Taipei City, Taiwan

Silicone Rubber Wire

- Designed for internal wiring in electrical and medical equipment which requires high temperature and voltage.
- Temperature rating : 150°C
- Voltage rating: 5KV
- UL style: 3239





Wonderful Hi-Tech Co., Ltd.



For more info Scan here!

Automobile Wire



ISO 6722 Standard

FLRY, FLY, FLR2X, FLR21X, FL2X, FL21X, FLR91X, FL91X, FLR7Y, FLR6Y, FLR51Y

JASO Standard

AV, AVS, AVSS, CAVS/CAVUS/CIVUS, AVX, AVSX, AVFX, AVXS, AVSSX, AVSSH, AEX, AESSX

SAE J-1128 Standard

GPT, GXL, TXL, SXL

Why Choose Us?

Wonderful Hi-Tech Advantages



Multi-Site Manufacturing (Taiwan/China/Thailand/Vietnam)



Technical Support



CCCA, TIA, BICSI Member




Experienced OEM MFR

F

Products are certified by International Lab



Product Diversity



Tel +886-2-2298-8033





Wonderful Hi-Tech Co., Ltd. (HQ) No. 72, Wugong 6th Road, New Taipei Industrial Park, Wugu District, New Taipei City, **Taiwan**

.

Tel +886-2-2298-8033